

(5) The arrangements for ventilation shall be such that during working hours in no part of the Cotton Cloth Factory shall the proportion of carbonic acid (carbon dioxide) in the air be greater than nine volumes of carbonic acid to every ten thousand volumes of air.

(6) Unless some other method certified by the Inspector to be equally satisfactory is adopted, the outside of the roof of every Cotton Cloth Factory shall be whitewashed every year before the 31st day of May, and such whitewash shall

be effectively maintained until the 31st day of August.

(7) In every Cotton Cloth Factory erected after the date of this Order, a sufficient and suitable cloak-room, or cloak-rooms, shall be provided for the use of all the persons employed therein, and shall be ventilated and kept at a suitable temperature.

M. W. RIDLEY.

Home Office, Whitehall, February 2, 1898.

SCHEDULE B.

FORM FOR RECORDING THE READINGS OF THE THERMOMETERS.

Name of Occupier _____

Address of Factory _____

Room { Number or Designation _____

{ Process carried on _____

{ Number of Operatives _____

{ Cubic contents _____ cubic feet.

Date.	READING OF THERMOMETERS <i>in degrees Fahrenheit.</i>						If no artificial humidity is produced in the 24 hours insert in this column "None."
	Between 7 and 8 A.M.		Between 10 and 11 A.M.		Between 3 and 4 P.M.		
	Dry Bulb.	Wet Bulb.	Dry Bulb.	Wet Bulb.	Dry Bulb.	Wet Bulb.	
Year.....							
Month and Day.							
1							
2							
3							
4							
5							
6							
7							
8							
9							
10							
11							
12							
13							
14							
15							
16							
17							
18							
19							
20							
21							
22							
23							
24							
25							
26							
27							
28							
29							
30							
31							

(Signed) _____

Occupier or Manager.